MATERIAL SAFETY DATA SHEET

SECTION 1 - PROD	OUCT IDENTI		AND USE	CII	DAIA	ouee i				
PRODUCT IDENTIFIER	IDENTIFICATION # 1209									
PRODUCT USE : CERAN	MIC GLAZE									
MANUFACTURER'S NAME	E SPECTRUM	GLAZES IN	IC.	SUPPLIER'S NAME SPECTRUM			CTRUM GI	LAZES INC.		
STREET ADDRESS: 273		STREET ADDRESS: 273 BOWES I			BOWES RI	D, UNIT A1				
CITY: CONCORD PROVINCE: ONTAR:			0	CITY: CONCORD PF			PROV	PROVINCE: ONTARIO		
POSTAL CODE: L4K1H8 EMERGENCY TEL) 695-8355		POSTAL CODE: L4K1H8 EMERGENCY TEL(905)695-8355					
SECTION 2 - HAZARDO	OUS INGREDI	ENTS								
HAZARDOUS INGREDIENTS		%	CAS NUMBER		LD50 OF INGREDIENTS (SPECIFY SPECIES AND ROUTE)			LC50 OF INGREDIENT (SPECIFY SPECIES)		
SiO2		30-35	14808-60-7		ILV 15mg/m3 OSHA/TWA					
K20		1-2	12136-45-7							
Ca0		10-13	1305-78-8							
Na2O		2-4	1313-59-3	3						
A1203		8-10	1344-28-1	L						
BaO		1-3	1304-28-5							
CERAMIC STAIN - BLA	ACK	3-5	1345-16-0)						
SECTION 3 - PHYSICA	AL DATA		•							
PHYSICAL STATE LIQUID	ODOUR AND	APPEARANCE LIQUID						ODOUR THRESHOLD (PPM) N.A.		
VAPOUR PRESSURE (mm Hg) N.A.	VAPOUR DE (AIR=1)			ION I	ION RATE BOILING		OINT(C)	FREEZING POINT(C)		
рн 6.5-7	SPECIFIC 1.6-2.0	GRAVITY	COEFF. W	ATER	ATER/OIL DIST.					
SECTION 4 - FIRE	AND EXPLOSI	ON DATA								
FLAMMABILITY YES	NO X FLAM	ES UNDER W	WHICH CONDI	TION	S: THIS	PRODUCT	DOES NOT	SUPPORT COMBUSTION		
MEANS OF EXTINCTION	NO SPECIA	L MEANS RE	EQUIRED							
FLASHPOINT AND METHOD NONE			UPPER FLAMMABLE LIMIT (% BY VOLUME) N.A.				LOWER FLAMMABLE LIMIT (% BY VOLUME) N.A.			
AUTOIGNITION TEMP.(C) N.A.			HAZARDOUS COMBUSTION PRODUCTS NONE							
EXPLOSION DATA N.A. SENSITIVITY IMPA			CT N.A. ACTIVITY TO STATIC DISCHARGE N.A.							
		SE	CTION 5 - I	REACI	TIVITY DA	TA				
CHEMICAL STABILITY	YES X NO	IF NO	O, UNDER WH	ICH	CONDITION	1S				
INCOMPATIBILITY WIT	TH OTHER SU	BSTANCES Y	YES NO X	I	F SO WHIC	CH ONESRE	ACTIVITY			
REACTIVITY AND UNDE	ER WHAT CON	DITIONS:NO) REACTIVIT	Ϋ́						
HAZARDOUS DECOMPOSI	ITION PRODU	CT: MATERI	IAL IS STAB					CIC FUMES MAY BE		
RELEASED WHEN				MA	TERIAL IS	MELTED.				

PRODUCT IDENTIFIER SPECTRUM LEAD FREE 1209 BLACK											
SECTION 6 - TOXICOLOGICAL PROPERTIES											
ROUTE OF ENTRY SKIN CONTACT SKIN ABSORPTION X EYE CONTACT X INHALATION INGESTION											
EFFECTS OF ACUTE EXPOSURE TO PRODUCT: SKIN IRRITATION DUE TO ABRASIVENESS. EYE EXPOSURE COULD CAUSE IRRITATION BUT NO TOXIC EFFECTS.											
EFFECTS OF CHRONIC EXPOSURE TO PRODUCT: METAL FUMES IN THE VAPOURS FROM FIRING CERAMIC GLAZES MAY CAUSE LUNG INFLAMATION AND DAMAGE TO KIDNEY AND NERVOUS SYSTEM.											
EXPOSURE LIMITS IRRITANO		CY OF PRODUCT	SENSITIZATION TO PRODUCT		CARCINOGENICITY						
TERATOGENCITY	RATOGENCITY REPRODU		MUTAGENICITY		SYNERGISTIC PRODUCTS						
SECTION 7 - PREVENTIVE MEASURES											
PERSONAL PROTECTIVE EQUIPMENT:											
GLOVES (SPECIFY) WORK GLOVES		RESPIRATOR (SPEC APPROVED DUST MA	· ·		EYE (SPECIFY) SAFETY GLASSES						
FOOTWEAR (SPECIFY)		CLOTHING (SPECIFY)		OTHER (SPECIFY)							
ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS) VENTILATION SHOULD BE USED WHEN SPRAYING GLAZES.											
LEAK AND SPILL PROCEDURE: SCOOP INTO SUITABLE RECEPTACLE. DO NOT WASH DOWN DRAIN.											
WASTE DISPOSAL: SEND TO APPROVED SITE IN ACCORDANCE WITH REGULATIONS.											
HANDLING PROCEDURES AND EQUIPMENT: NO SPECIAL EQUIPEMENT NEEDED. FOLLOW STANDARD PLANT HYGIENE PROCEDURE.											
STORAGE REQUIREMENTS: STORE IN DRY AREAS.											
SPECIAL SHIPPING INFORMATION: PROTECT AGAINST PHYSICAL DAMAGE. DOT LABEL NON-REGULATED											
		SECTION 8 - FIR	ST AID MEASURES								
SPECIFIC MEASURES: GLAZE CONTAINS THE OXIDES LISTED IN THE CHEMICAL FORMULA IN FORM OF CERAMIC FRIT. SOME OF THESE OXIDES ARE ON THE INGREDIENT DISCLOSURE LIST, ONCE THESE OXIDES ARE FUSED AND CONVERTED INTO FRIT THEY ARE NO LONGER AVAILABLE IN TOXIC FORM EVEN THOUGH TESTING WOULD DETECT THE PRESENCE OF THESE OXIDES. (FRIT IS ESSENTIALLY AN INSOLUBLE SUBSTANCE). THE OXIDES ARE PRESENT IN THE FORM OF A SINTERED CERAMIC STAIN OF LOW SOLUBILITY. THESE INGREDIENTS ARE PRESENT IN A STABLE AQUEOUS SUSPENSION.											
SECTION 9 - PREPARATION DATE OF MSDS											
PREPARED BY (GROUP, DEPARTMENT, ETC.) TECHNICAL DEPT.		PHONE NUMBER: (905) 695-8355		DATE 1 AUGUS	г 2015						